

# SAFES

## ROBUR I-340



### **Burglary protection**

The safe is tested in accordance with the European standard EN-1143-1 and certified by ECB·S.

### **Fire protection**

The Safe is tested in accordance with the European standard EN-15659 LFS 30 P and certified by ECB·S

### **Description**

Solid barrier material in the door and body.

### **Locking**

As standard the safe is provided with one changeable key-lock type FAS/S&G 6890.

Available as option:

Combination lock type S&G 8550MP,  
Electronic combination lock type Wittkopp.

### **Finish**

Off white, RAL 9010.

### **Weight and measurement**

See overleaf

# Dimensions in mms and kilos

<b>Safe Robur I - 340</b>	
<b>External measurements mm</b>	
Height	340
Width	500
Depth (plus 50 mm for handle)	345
<b>Internal measurements mm</b>	
Height	262
Width	424
Depth	216
<b>Weight kilos</b>	93
<b>Volume litre</b>	24

We reserve the right to alter the specification without prior notice.



**Head office**  
**Robur Safe AB**  
Lundbyvägen 8  
SE-310 50 SLÖINGE  
Phone: +46 346 260 260  
Fax: +46 346 260 222

[info@robursafe.com](mailto:info@robursafe.com)

[www.robursafe.com](http://www.robursafe.com)