



Robur S2 Safes - 30P



Burglary protection

Burglary-resistance – S2 according to EN 14450

Fire protection

Fire-resistance – LFS 30P according to EN 15659

Description

Designed to protect documents and valuables in case of fire or burglary

Thickness of door - 92mm

Thickness of walls - 56mm

Space between walls and door filled with fire-resistant concrete

3 live-locking bolts

Integrated relocker, lock secured from drill attacks

Standard delivery with double-bit high security key lock with two keys

Locking

KL - Key lock

EL - Digital lock

Finish

Off white, powder coating, RAL 9010.

Weight and measurements

See overleaf.

Dimensions in mms and kilos

| model | Robur S2-320/30 | Robur S2-460/30 | Robur S2-670/30 | Robur S2-950/30 |
|-------------------------|------------------------|------------------------|------------------------|------------------------|
| External dimensions, mm | | | | |
| Height | 315 | 460 | 670 | 950 |
| Width | 445 | 440 | 440 | 440 |
| Depth | 440 | 440 | 440 | 440 |
| Internal dimensions, mm | | | | |
| Height | 185 | 330 | 540 | 820 |
| Width | 334 | 329 | 329 | 329 |
| Depth | 290 | 290 | 290 | 290 |
| Weight | 52 | 68 | 91 | 120 |
| Capacity, litre | 18 | 31 | 52 | 78 |
| Number of shelves | 1 | 1 | 1 | 2 |

We reserve the right to alter the specification without prior notice.



Head office

Robur Safe AB

Lundbyvägen 8
SE-310 50 SLÖINGE
Phone: +46 346 260 260
Fax: +46 346 260 222

info@robursafe.com

www.robursafe.com