



Robur S2 Safes - 60P



Burglary protection

Burglary-resistance – S2 according to EN 14450

Fire protection

Fire-resistance – LFS 60P according to EN 15659

Description

Designed to protect documents and valuables in case of fire or burglary

Thickness of door - 92mm

Thickness of walls - 56mm

Space between walls and door filled with fire-resistant concrete

3 live-locking bolts

Integrated relocker, lock secured from drill attacks

Standard delivery with double-bit high security key lock with two keys

Locking

KL - Key lock

EL - Digital lock

Finish

Off white, powder coating, RAL 9010.

Weight and measurements

See overleaf.

Dimensions in mms and kilos

model	Robur S2-320/60	Robur S2-460/60	Robur S2-670/60
External dimensions, mm			
Height	345	490	670
Width	480	480	480
Depth	460	480	480
Internal dimensions, mm			
Height	185	330	540
Width	332	332	332
Depth	300	300	300
Weight	64	81	103
Capacity, litre	18	32	53
Number of shelves	1	1	1

We reserve the right to alter the specification without prior notice.



Head office

Robur Safe AB

Lundbyvägen 8
SE-310 50 SLÖINGE
Phone: +46 346 260 260
Fax: +46 346 260 222

info@robursafe.com

www.robursafe.com