



SAFES ROBUR I, II, III



Grade I & II



Grade III

Burglary protection

The safes are tested in accordance with the European standard EN-1143-1 and certified by SBSC and ECB·S.

Fire protection

The safes in models: 40, 50, 80, 500, 900, 1200 and 1500 are tested and classified in accordance with NT Fire 017 - 60P.

Description

Solid barrier material in the door and body.

Weight and measurement

See overleaf

Locking

As standard the safe is provided with one changeable key-lock.

Available as option:

Combination lock and

Electronic combination lock.

Finish

Off white, RAL 9010.

Fittings


See overleaf

Dimensions in mms and kilos


Safe Robur I & II							
Model	40	50	80	500	900	1200	1500
External measurements mm							
Height	558	633	933	633	1033	1333	1623
Width	535	535	535	635	635	635	635
Depth *	531	531	531	601	601	601	601
Internal measurements mm							
Height	425	500	800	500	900	1200	1490
Width	400	400	400	500	500	500	500
Depth	330	330	330	400	400	400	400
Weight Grade I kilos	180	195	235	220	355	425	500
Weight Grade II kilos	290	325	425	395	570	700	830
Volume litre	56	66	105	100	180	240	300
Standard fittings	1 shelf	1 shelf	2 shelves	1 shelf	2 shelves	2 shelves	3 shelves

Safe Robur III									
Model	40	50	80	500	900	1200	1500	1800/2	1800/3
External measurements mm									
Height	545	645	945	645	1045	1345	1545	1965	1965
Width	540	540	540	640	640	640	640	870	1190
Depth *	584	584	584	654	654	654	654	794	794
Internal measurements mm									
Height	400	500	800	500	900	1200	1500	1820	1820
Width	400	400	400	500	500	500	500	730	1050
Depth	330	330	330	400	400	400	400	540	540
Weight kilo	325	375	520	450	680	830	980	1600	2050
Standard fittings	1 shelf	1 shelf	2 shelves	1 shelf	2 shelves	2 shelves	3 shelves	3 shelves	3 shelves

INTERIOR FITTINGS



Lockable drawer



Lockable cupboard




Combination lock
S&G 8550 MP



Extra shelf



Electronic pincode lock



Sliding frame



Security cupboard

Interior fittings	External height mm
A. Shelf	-
B. Lockable cupboard, small	155
C. Lockable cupboard, large	355
D. Sliding frame for A4/folio	-
E. Security cupboard	420
F. Lockable drawer, small	155
G. Lockable drawer, large	355

We reserve the right to alter the specification without prior notice.



Head office
Robur Safe AB
 Lundbyvägen 8
 SE-311 68 SLÖINGE
 Phone: +46 346 260 260
 Fax: +46 346 260 222

info@robursafe.com

www.robursafe.com